

UL1061 Hook-up Wire 连接线

Tinned or bare, stranded or solid copper conductor, 30-10 AWG, Lead free SR-PVC insulation

导体使用 30-10 AWG 单根或绞合裸铜或镀锡铜线, 半硬质无铅聚氯乙烯绝缘

PRODUCT DESCRIPTION 产品说明



E148000 AWM STYLE 1061 AWG NO. 80C 300V VW-1 --- AWM I A/B 80C 300V FT1 -F- -LF- PCXX LTK

- Rated temperature 额定温度 : 80°C
- Rated voltage 额定电压 : 300V
- Reference standard 参考标准 :
UL 758, UL1581 & CSA C22.2 No. 210
- Passes UL VW-1 & CSA FT1 vertical flame test
通过 UL VW-1 及 CSA FT1 垂直耐燃测试
- Halogen-free Substitution: UL10368 & UL10981
无卤物料替代方案 : UL10368 及 UL10981

Conductor 导体			Insulation 绝缘		Max. DC Resistance at 20°C 最大电阻 (ohm/km)
AWG 线规	No./mm 线数/线径	Diameter 线径 (mm)	Thickness 厚度 (mm)	Diameter 外径 (mm)	
30	7/0.10	0.30	0.26	0.82	381
28	7/0.127	0.38	0.26	0.90	239
26	7/0.16	0.48	0.26	1.00	150
24	11/0.6	0.61	0.27	1.15	94.2
22	17/0.16	0.76	0.26	1.28	59.4
20	26/0.16	0.94	0.26	1.46	36.7
18	41/0.16	1.18	0.26	1.70	23.2
16	26/0.254	1.49	0.26	2.02	14.6


UL1185 Single Conductor Shielded Cable 单芯屏蔽电缆

Tinned or bare, stranded or solid copper conductor, 30-4/0 AWG,

Tinned or bare copper wire spiral shield, Lead free PVC insulation

导体使用 30-4/0 AWG 单根或绞合裸铜或镀锡铜线, 镀锡铜或裸软铜线斜包屏蔽, 无铅聚氯乙烯绝缘

PRODUCT DESCRIPTION 产品说明



E148000 AWM STYLE 1185 AWG NO. 80C 300V VW-1 --- AWM I A/B 80C 300V FT1 -F- -LF- PCXX LTK

- Rated temperature 额定温度 : 80°C
- Rated voltage 额定电压 : 300V
- Reference standard 参考标准 :
UL 758, UL1581 & CSA C22.2 No.210
- Passes UL VW-1 & CSA FT1 vertical flame test
通过 UL VW-1 及 CSA FT1 垂直耐燃测试
- Halogen-free Substitution: UL10800 & UL10983
无卤物料替代方案 : UL10800 及 UL10983

Conductor 导体			Insulation 绝缘		Spiral Shield 斜包屏蔽		Jacket 护套		Max. DC Resistance at 20°C 最大电阻 (ohm/km)
AWG 线规	No./mm 线数/线径	Diameter 线径 (mm)	Thickness 厚度	Diameter 外径 (mm)	No./mm 线数/线径	Diameter 外径 (mm)	Thickness 厚度 (mm)	Diameter 外径 (mm)	
28	7/0.127	0.38	0.43	1.24	38/0.1	1.44	0.45	2.34	239
26	7/0.16	0.48	0.43	1.34	45/0.1	1.54	0.45	2.44	150
24	11/0.16	0.61	0.43	1.47	46/0.1	1.67	0.46	2.58	94.2
22	17/0.16	0.76	0.43	1.62	54/0.1	1.82	0.46	2.74	59.4
20	26/0.16	0.94	0.43	1.80	56/0.1	2.00	0.46	2.92	36.7
18	41/0.16	1.18	0.43	2.04	64/0.1	2.24	0.46	3.16	23.2
16	26/0.254	1.49	0.43	2.36	74/0.1	2.56	0.46	3.48	14.6



1. Only part of products are listed above.

以上表格只列出一部份产品。

2. The above information is for reference only, and is subject to the final specification.

以上数字仅为参考值, 数字以最终规格书为准。